



WM.W. NUGENT & CO. (INC)

3440 CLEVELAND STREET
SKOKIE, IL 60076-0948

E-mail:
Sales@wwnugent.com

Phone: 847-674-7782
www.nugentfilters.com

SERIES : 1577

SIZE : 1

**MANUFACTURERS OF NUGENT PATENTED LIQUID FILTERS AND STRAINERS,
FILTERING SYSTEMS, AND SIGHT FLOW INDICATORS**

PART# : 01-094-025



MODEL# : CG18

REVISION : 12/25

E-MAIL: SALES@WWNUGENT.COM WITH ANY QUESTIONS ABOUT SIZING OR FLOW

PLEATED MICROGLASS FILTER ELEMENT WITH METAL OUTER WRAP

TECHNICAL DATA

PARTICLE RETENTION : 50 MICRON

NOMINAL DIMENSIONS :

INNER CORE : N/A

Length : 19-7/16"

GASKET MATERIAL : NEOPRENE

I/D : 1-15/32"

O-RING MATERIAL: BUNA

O/D : 6"

FLOW DIRECTION : INSIDE - OUT

BURST PRESSURE : 70 PSID

RECOMMENDED PRESSURE DROP - \leq 5 PSID

RECOMMENDED PRESSURE DROP - DIRTY : 25 PSID

RECOMMENDED FLOW RATE PER ELEMENT : 60 GPM @ 150 SSU

NOTES : MAX TEMPERATURE: 200° F

25-Micron Version (Nugent P/N 01-094-026)