



WM.W. NUGENT & CO. (INC)

3440 CLEVELAND STREET E-mail:
SKOKIE, IL 60076-0948 Sales@wwnugent.com

Phone: 847-674-7782
www.nugentfilters.com

SERIES : 1577

SIZE : 2

**MANUFACTURERS OF NUGENT PATENTED LIQUID FILTERS AND STRAINERS,
FILTERING SYSTEMS, AND SIGHT FLOW INDICATORS**

PART# : 01-535-020



MODEL# : BC

REVISION : 02/26

E-MAIL: SALES@WWNUGENT.COM WITH ANY QUESTIONS ABOUT SIZING OR FLOW

PLEATED MICROGLASS FILTER ELEMENT

TECHNICAL DATA

PARTICLE RETENTION : 1 MICRON NOMINAL

NOMINAL DIMENSIONS :

INNER CORE : ELECTRO - COATED

Length : 36-1/2"

GASKET MATERIAL : NEOPRENE

I/D : 2-5/8" (TOP) / 3-1/2" (BTM.)

O-RING MATERIAL : N/A

O/D : 6"

FLOW DIRECTION : OUTSIDE - IN

COLLAPSE PRESSURE : 100 PSID

RECOMMENDED PRESSURE DROP - \leq 5 PSID

RECOMMENDED PRESSURE DROP - DIRTY : 25 PSID

RECOMMENDED FLOW RATE PER ELEMENT : 300 GPM @ 220 SSU

NOTES :