



WM.W. NUGENT & CO. (INC)

3440 CLEVELAND STREET
SKOKIE, IL 60076-0948

E-mail:
Sales@wwnugent.com

Phone: 847-674-7782
www.nugentfilters.com

SERIES : 1577

SIZE : 4L

**MANUFACTURERS OF NUGENT PATENTED LIQUID FILTERS AND STRAINERS,
FILTERING SYSTEMS, AND SIGHT FLOW INDICATORS**

PART# : 01-688-006



MODEL# : XB

REVISION : 12/25

E-MAIL: SALES@WWNUGENT.COM WITH ANY QUESTIONS ABOUT SIZING OR FLOW

PLEATED MICROGLASS FILTER ELEMENT

TECHNICAL DATA

PARTICLE RETENTION : 1 MICRON NOMINAL

NOMINAL DIMENSIONS :

INNER CORE : ELECTRO-COATED

Length : 30-5/16"

**GASKET MATERIAL : BUNA-N (TOP),
NEOPRENE (BOTTOM)**

I/D : 3-3/8" (BOTTOM)

O-RING MATERIAL: VITON

O/D : 6"

FLOW DIRECTION : OUTSIDE - IN

COLLAPSE PRESSURE : 100 PSID

RECOMMENDED PRESSURE DROP - ≤ 5 PSID

RECOMMENDED PRESSURE DROP - DIRTY : 25 PSID

RECOMMENDED FLOW RATE PER ELEMENT : 300 GPM @ 250 SSU

NOTES :