



WM.W. NUGENT & CO. (INC)

3440 CLEVELAND STREET
SKOKIE, IL 60076-0948

E-mail:
Sales@wwnugent.com

Phone: 847-674-7782
www.nugentfilters.com

SERIES : 1554

SIZE : 4L

**MANUFACTURERS OF NUGENT PATENTED LIQUID FILTERS AND STRAINERS,
FILTERING SYSTEMS, AND SIGHT FLOW INDICATORS**

PART# : 30-055-201



MODEL# : 4L-2140

REVISION : 12/25

E-MAIL: SALES@WWNUGENT.COM WITH ANY QUESTIONS ABOUT SIZING OR FLOW

CYLINDRICAL STRAINER ELEMENT

TECHNICAL DATA

PARTICLE RETENTION : 25 MICRON	NOMINAL DIMENSIONS :	ITEM NO.	STRAINER BASKET ASSEMBLY PART
GASKET MATERIAL : COMPRESSED SHEET	Length : 30"	1	1 P/N 30-300-201 STRAINER CYLINDER
O-RING MATERIAL: BUNA-N	I/D : 3"	2	1 P/N 30-004-203 SPOOL
FLOW DIRECTION : INSIDE-OUT	O/D : 6"	3	1 P/N 30-058-001 COVER
BURST PRESSURE : 150 PSID		4	1 P/N 30-053-001 WING NUT
RECOMMENDED PRESSURE DROP - 2 PSID		5	1 P/N 01-061-011 O-RING
RECOMMENDED PRESSURE DROP - DIRTY : 8 PSID		6	1 P/N 01-047-004 GASKET
RECOMMENDED FLOW RATE PER ELEMENT : 130 GPM @ 200 SUS			

NOTES :

Furnished with optional 10 micron Pleated Element Insert (P/N 01-290-001): 100 GPM @ 150 SUS = 2 psid