



WM.W. NUGENT & CO. (INC)

3440 CLEVELAND STREET
SKOKIE, IL 60076-0948

E-mail:
Sales@wwnugent.com

Phone: 847-674-7782
www.nugentfilters.com

SERIES : 1554

SIZE : 4L

**MANUFACTURERS OF NUGENT PATENTED LIQUID FILTERS AND STRAINERS,
FILTERING SYSTEMS, AND SIGHT FLOW INDICATORS**

PART# : 30-055-203



MODEL# : 4L-200

REVISION : 1/26

E-MAIL: SALES@WWNUGENT.COM WITH ANY QUESTIONS ABOUT SIZING OR FLOW

CYLINDRICAL STRAINER ELEMENT

TECHNICAL DATA

PARTICLE RETENTION : 74 MICRON

NOMINAL DIMENSIONS :

ITEM NO.

**STRAINER BASKET ASSEMBLY
PART**

GASKET MATERIAL : DURABLA

Length : 30"

1

**1 P/N 30-300-203 STRAINER
CYLINDER**

O-RING MATERIAL: BUNA-N

I/D : 3"

2

1 P/N 30-004-203 SPOOL

FLOW DIRECTION : INSIDE-OUT

O/D : 6"

3

1 P/N 30-058-001 COVER

BURST PRESSURE : 150 PSID

4

1 P/N 30-053-001 WING NUT

RECOMMENDED PRESSURE DROP - 2 PSID

5

1 P/N 01-061-011 O-RING

RECOMMENDED PRESSURE DROP - DIRTY : 8 PSID

6

1 P/N 01-047-004 GASKET

RECOMMENDED FLOW RATE PER ELEMENT : 300 GPM @ 300 SUS

NOTES :

OPTIONAL: For Flushing: 10 micron pleated paper element insert (P/N 01-290-001): @ 100 GPM @ 150 SUS = 2 psid